


**MATERIAL SAFETY DATA SHEET**

For U.S. Manufactured or Distributed Welding Consumables and Related Products. May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200 and Superfund Amendments and Reauthorization Act (SARA) of 1986 Public Law 99-499. Standard must be consulted for specific requirements.

**SECTION 1 – IDENTIFICATION**

Manufacturer/Supplier Name: HOBART BROTHERS  
 Address: 400 TRADE SQUARE EAST, TROY, OH 45373  
 Trade Name: FROGALLOY, HARDALLOY, SMOOTHARC, CHROME-MANG, AND GP HARDSURFACING ELECTRODES  
 Product Type for: HARDSURFACING ELECTRODES

Telephone No: (937) 332-4000  
 Emergency No: (800) 424-9300  
 Classification: None

**SECTION 2 - HAZARDOUS INGREDIENTS**

**IMPORTANT** - This section covers the hazardous ingredients from which this product is manufactured. The fumes and gases produced during welding with normal use of this product are also addressed in Section 5. The term "hazardous" in this section should be interpreted as a term required and defined in OSHA Hazard Communication Standard (29 CFR Part 1910.1200).

HAZARDOUS INGREDIENTS	% WEIGHT	CAS NO.	EXPOSURE LIMIT (mg/m <sup>3</sup> ) OSHA PEL	ACGIH TLV
IRON+	40-80	7439-89-6	5 R* 10 (Oxide Fume)	3R* 5 R* (Oxide) {A4}
CALCIUM CARBONATE	0-10	1317-65-3	5 R* 5 (as CaO)	10 ◆◆◆◆◆ 2 (as CaO)
FLUORSPAR	0-10	7789-75-5	2.5 (as F)	2.5 (as F) {A4}
TITANIUM DIOXIDE	0-17	13463-67-7	15 (Dust)	10 {A4}
MOLYBDENUM	0-6	7439-98-7	5 R*	3 R*; 10 I* (Elemental and Insoluble)
CHROMIUM#	7-35	7440-47-3	1 (Metal) 0.5 (Cr II & Cr III Compounds) 0.005 (Cr VI Compounds)	0.5 R* (Soluble Compounds) {A3} 0.5 (Metal) {A4} 0.5 (Cr III Compounds) {A4} 0.05 (Cr VI Soluble Compounds) {A1} 0.01 (Cr VI Insoluble Compounds) {A1}
SILICA++ (Amorphous Silica Fume)	1-10	14808-60-7 69012-64-2	0.1 R* 0.8	0.025 R* {A2} 3 R* ◆◆◆
TUNGSTEN compounds)	0-1	7440-33-7	5 R*	5, 10 STEL*** (Metal and Insoluble)
MANGANESE#	0.5-15	7439-96-5	5 CL** (Fume) 1, 3 STEL*** (Fume)	1, 3 STEL*** (Soluble compounds) 0.2 (Dust & Fume)
SILICON+	<8	7440-21-3	5 R*	3 R* ◆◆◆
TITANIUM+	0-5	7440-32-6	5 R*	3R*
ALUMINUM###	0-3	7429-90-5	5 R*	10 2 (soluble salts as Al)
MAGNESIUM CARBONATE	0-5	546-93-0	5 R*	3 R* ◆◆◆
NICKEL#	0-10	7440-02-0	1 (Metal) 1 (Soluble Compounds) 1 (Insoluble Compounds)	1.5 I* (Metal) {A5} 0.1 I* (Soluble Compounds) {A4} 0.2 I* (Insoluble Compounds) {A1}
COLUMBIUM+	0-4	7440-03-1	5 R*	3R*
SILICATE BINDERS	<5	-----	Not Established	Not Established

R\* - Respirable Fraction. I\* - Inhalable Fraction \*\* - Ceiling Limit. \*\*\* - Short Term Exposure Limit. +- As a nuisance particulate covered under "Particulates Not Otherwise Regulated" by OSHA or "Particulates Not Otherwise Classified" per ACGIH. ++ - Crystalline silica is bound within the product as it exists in the package. However, research indicates silica is present in welding fume in the amorphous (noncrystalline) form # - Reportable material under Section 313 of SARA. ### - Reportable material under Section 313 of SARA as dust or fume. {A1} - Confirmed Human Carcinogen per ACGIH {A3} - Confirmed Animal Carcinogen with Unknown Relevance to Humans per ACGIH {A4} - Not Classifiable as a Human Carcinogen per ACGIH {A5} - Not Suspected as a Human Carcinogen per ACGIH ◆◆◆ - TLV withdrawn in 2006 per ACGIH ◆◆◆◆◆ - Intention to withdraw TLV in 2006 per ACGIH  
**The exposure limit for welding fume has been established at 5 mg/m<sup>3</sup> with OSHA's PEL and ACGIH's TLV. The individual complex compounds within the fume may have lower exposure limits than the general welding fume PEL/TLV. An Industrial Hygienist, the OSHA Permissible Exposure Limits For Air Contaminants (29 CFR 1910.1000), and the ACGIH Threshold Limit Values should be consulted to determine the specific fume constituents present and their respective exposure limits.**

**SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS**

Welding consumables applicable to this sheet as shipped are solid and nonvolatile as shipped.

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

Welding consumables applicable to this sheet as shipped are nonreactive, nonflammable, nonexplosive and essentially nonhazardous until welded. Welding arcs and sparks can ignite combustibles and flammable products. See American National Standard Z49.1 referenced in Section 7.

## HARDSURFACING

### SECTION 5 - REACTIVITY DATA

#### HAZARDOUS DECOMPOSITION PRODUCTS

Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedures and electrodes used. **Most fume ingredients are present as complex oxides and compounds and not as pure metals.**

Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coatings on the metal being welded (such as paint, plating or galvanizing), the number of welders and the volume of the work area, the quality and amount of ventilation, the position of the welder's head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from cleaning and degreasing activities).

When the electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 2. Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 2, plus those from the base metal and coating, etc., as noted above.

Reasonably expected constituents of the fume would include: Primarily - iron oxides. Secondarily - complex oxides of calcium, fluorides, titanium, molybdenum, chromium and nickel compounds, silicon, tungsten, manganese, aluminum, magnesium, and columbium.

Monitor for the materials identified in Section 2. **Fumes from the use of these products may contain chromium, nickel, manganese, fluorides, calcium oxides, amorphous silica fume, and tungsten which have exposure limits lower than the 5 mg/m<sup>3</sup> PEL/TLV for general welding fume.**

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc.

One recommended way to determine the composition and quantity of fumes and gases to which workers are exposed is to take an air sample inside the welder's helmet if worn or in the worker's breathing zone. [See ANSI/AWS F1.1, available from the "American Welding Society", P.O. Box 351040, Miami, FL 33135. Also, from AWS is F1.3 "Evaluating Contaminants in the Welding Environment - A Sampling Strategy Guide", which gives additional advice on sampling.]

### SECTION 6 - HEALTH HAZARD DATA

#### EFFECTS OF OVEREXPOSURE:

Electric arc welding may create one or more of the following health hazards:

ARC RAYS can injure eyes and burn skin.

FUMES AND GASES can be dangerous to your health.

ELECTRIC SHOCK can kill. See Section 7.

PRIMARY ROUTES OF ENTRY are the respiratory system, eyes and/or skin.

#### SHORT-TERM (ACUTE) OVEREXPOSURE EFFECTS:

WELDING FUMES - May result in discomfort such as dizziness, nausea or dryness or irritation of nose, throat or eyes.

IRON, IRON OXIDE - None are known. Treat as nuisance dust or fume.

CALCIUM OXIDE - Dust or fumes may cause irritation of the respiratory system, skin and eyes.

FLUORIDES - Fluoride compounds evolved may cause skin and eye burns, pulmonary edema and bronchitis.

TITANIUM DIOXIDE - Irritation of respiratory system.

MOLYBDENUM - Irritation of the eyes, nose and throat.

CHROMIUM - Inhalation of fume with chromium (VI) compounds can cause irritation of the respiratory tract, lung damage and asthma-like symptoms. Swallowing chromium (VI) salts can cause severe injury or death. Dust on skin can form ulcers. Eyes may be burned by chromium (VI) compounds. Allergic reactions may occur in some people.

SILICA (AMORPHOUS) - Dust and fumes may cause irritation of the respiratory system, skin and eyes.

TUNGSTEN - Dust may cause irritation of the skin and eyes. Inhalation of dust may cause acute airways obstructive asthma which is reversible following overexposure. Symptoms are tightening chest and productive cough.

MANGANESE - Metal fume fever characterized by chills, fever, upset stomach, vomiting, irritation of the throat and aching of body. Recovery is generally complete within 48 hours of the overexposure.

ALUMINUM, ALUMINUM OXIDE - Irritation of the respiratory system.

MAGNESIUM, MAGNESIUM OXIDE - Overexposure to the oxide may cause metal fume fever characterized by metallic taste, tightness of chest and fever. Symptoms may last 24 to 48 hours following overexposure.

NICKEL, NICKEL COMPOUNDS - Metallic taste, nausea, tightness in chest, metal fume fever, allergic reaction.

COLUMBIUM - Dust or fumes may cause irritation of the respiratory system, skin and eyes.

#### LONG-TERM (CHRONIC) OVEREXPOSURE EFFECTS:

WELDING FUMES - Excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis or "siderosis."

IRON, IRON OXIDE FUMES - Can cause siderosis (deposits of iron in lungs) which some researchers believe may affect pulmonary function. Lungs will clear in time when exposure to iron and its compounds ceases. Iron and magnetite (Fe<sub>3</sub>O<sub>4</sub>) are not regarded as fibrogenic materials.

CALCIUM OXIDE - Prolonged overexposure may cause ulceration of the skin and perforation of the nasal septum, dermatitis and pneumonia.

FLUORIDES - Serious bone erosion (Osteoporosis) and mottling of teeth.

TITANIUM DIOXIDE - Pulmonary irritation and slight fibrosis.

MOLYBDENUM - Prolonged overexposure may result in loss of appetite, weight loss, loss of muscle coordination, difficulty in breathing and anemia.

CHROMIUM - Ulceration and perforation of nasal septum. Respiratory irritation may occur with symptoms resembling asthma. Studies have shown that chromate production workers exposed to hexavalent chromium compounds have an excess of lung cancers. Chromium (VI) compounds are more readily absorbed through the skin than chromium (III) compounds. Good practice requires the reduction of employee exposure to chromium (III) and (VI) compounds.

SILICA (AMORPHOUS) - Research indicates that silica is present in welding fume in the amorphous form. Long term overexposure may cause pneumoconiosis. Noncrystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.

TUNGSTEN - Long term overexposure may cause pulmonary fibrosis characterized by a rapid onset of cough, sputum and dyspnea on exertion.

MANGANESE - Long term overexposure to manganese compounds may affect the central nervous system. Symptoms may be similar to Parkinson's Disease and can include slowness, changes in handwriting, gait impairment, muscle spasms and cramps and less commonly, tremor and behavioral changes. Employees who are exposed to manganese compounds should be seen by a physician for early detection of neurologic problems.

ALUMINUM, ALUMINUM OXIDE - Pulmonary fibrosis and emphysema.

MAGNESIUM, MAGNESIUM OXIDE - No adverse long term health effects have been reported in the literature.

NICKEL, NICKEL COMPOUNDS - Lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers.

COLUMBIUM - No adverse long term health effects have been reported in the literature.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with pre-existing impaired lung functions (asthma-like conditions).

**EMERGENCY AND FIRST AID PROCEDURES:** Call for medical aid. Employ first aid techniques recommended by the American Red Cross.

Eyes & Skin: If irritation or flash burns develop after exposure, consult a physician.

**CARCINOGENICITY:** Chromium VI and nickel compounds must be considered carcinogens according to OSHA (29 CFR 1910.1200). Chromium VI compounds are classified as IARC Group 1 and NTP Group 1 carcinogens. Nickel compounds are classified as IARC Group 1 and NTP Group 2 carcinogens. Welding fumes must be considered as possible carcinogens under OSHA (29 CFR 1910.1200).

**CALIFORNIA PROPOSITION 65:** WARNING: These products contain or produce chemicals known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code Section 25249.5 et seq.)

**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING & USE/APPLICABLE CONTROL MEASURES**

Read and understand the manufacturer's instructions and the precautionary label on the product. See American National Standard Z49.1; Safety in Welding and Cutting published by the American Welding Society, P.O. Box 351040, Miami, FL 33135 and OSHA Publication 2206 (29 CFR 1910), U.S. Government Printing Office, Washington, DC 20402 for more detail on any of the following.

**VENTILATION:** Use enough ventilation, local exhaust at the arc or both to keep the fumes and gases below PEL/TLVs in the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes.

**RESPIRATORY PROTECTION:** Use NIOSH approved or equivalent fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below PEL/TLVs.

**EYE PROTECTION:** Wear helmet or use face shield with filter lens. As a rule of thumb begin with Shade Number 14. Adjust if needed by selecting the next lighter and/or darker shade number. Provide protective screens and flash goggles, if necessary, to shield others.

**PROTECTIVE CLOTHING:** Wear hand, head and body protection which help to prevent injury from radiation, sparks and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection as well as dark nonsynthetic clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground.

**PROCEDURE FOR CLEANUP OF SPILLS OR LEAKS:** Not applicable

**WASTE DISPOSAL:** Prevent waste from contaminating surrounding environment. Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with Federal, State and Local regulations.

**SPECIAL PRECAUTIONS (IMPORTANT):** Maintain exposure below the PEL/TLVs. Use industrial hygiene monitoring to ensure that your use of this material does not create exposures which exceed PEL/TLVs. Always use exhaust ventilation. Refer to the following sources for important additional information: ANSI Z49.1 from the American Welding Society, P.O. Box 351040, Miami, FL 33135 and OSHA (29 CFR 1910) from the U.S. Department of Labor, Washington, DC 20210.

**Hobart Brothers believes this data to be accurate and to reflect expert opinion regarding current research. However, Hobart Brothers cannot make any expressed or implied warranty as to this information.**