**S**afety Latest Revision: June 2015

**D**ata Page 1 of 7

**S**heet Hobart Brothers Co.

# 

## 1. PRODUCT AND COMPANY IDENTIFICATION:

**PRODUCT NAME:** Electrodes, 6013 (H117119-RDP, H117125-RDP, H117132-R01, H117144-R01)

SUPPLIER: Hobart Brothers Co. 2200 Corporate Drive Troy, OH 45373 U.S.A. Phone: 937-332-4000

> E-mail: info@hobartwelders.com Website: www.hobartwelders.com

EMERGENCY TELEPHONE NUMBER: 1-800-424-9300 (Chemtrec CCN11662)

### 2. HAZARD IDENTIFICATION:

**Emergency Overview:** This product is normally not considered hazardous as shipped. Avoid eye contact or inhalation of dust from the product. When this product is used in a welding process, the most important hazards are welding fumes, heat, radiation and electric shock.

Classification of the Substance/Mixture

CLP/GHS Classification (1272/2008):

Carcinogenicity, Category 2

EU Classification (67/548/EEC):

Harmful (Xn), Carcinogen Category 3, R40

Hazardous Classification per 29CFR 1910.1200 (Rev. July 1, 2012):

Carcinogenicity, Category 2

Labelling:

Symbols:

Signal Word: Warning

Hazard-determining components of labelling:

**Titanium Dioxide** 

**Hazard Statements:** 

H351 - Suspected of causing cancer.

**Precautionary Statements:** 

**P201** – Obtain special instructions before use.

**P202** – Do not handle until all safety precautions have been read and understood.

**P280** – Wear protective gloves/eye protection/face protection.

P281 – Use personal protective equipment as required.

P308+P313 – IF exposed or concerned: Get medical advice/attention.

**P402+P404** – Store in a dry place. Store in a closed container.

**P405** – Store locked up.

**P501** – Dispose of contents/container in accordance with local/regional/national/international regulations.

Hobart Brothers Co.

**S**afety Latest Revision: June 2015

**D**ata Page 2 of 7

# 

## 3. COMPOSITION / INFORMATION ON INGREDIENTS:

Chemical Identity	CAS#	Range %	OSHA PEL (mg/m3)	ACGIH-TLV (mg/m3)	Carcinogenicity	EU Classification (67/548/EEC)	CLP/GHS Classification (1272/2008)	Hazardous Classification per 29CFR 1910.1200 (Rev. July, 2012)
Kaolin	1332-58-7	1-11	10	2	No	Not Dangerous	Not Hazardous	Not Hazardous
Cellulose	9004-34-6	1-11	NR	10	No	Not Dangerous	Not Hazardous	Not Hazardous
Feldspar	68476-25-5	1-11	NR	NR	No	Not Dangerous	Not Hazardous	Not Hazardous
#Manganese	7439-96-5	1-11	5	1	No	<b>≭</b> (Xn) R48	(H373) STOT RE 2	(H373) STOT RE 2
Titanium Dioxide	13463-67-7	5-15	15	10	No	Carc. Cat. 3;	(H351) Carc. 2	(H351) Carc. 2
Potassium Silicate	1312-76-1	1-11	NR	5	No	X(Xi) R36/38	(H315) Skin Irrit 2	(H315) Skin Irrit 2 (H319) Eye Irrit 2A
Iron	7439-89-6	65-75	10 ( as Fe2O3 )	10 ( as Fe2O3 )	No	Not Dangerous	Not Hazardous	Not Hazardous

Important This section covers the materials of which the products manufactured. The fumes and gases produced during normal use of this product are covered in section 10. The term "Hazardous" in "Hazardous Material" should be interpreted as a term required and defined in OSHA Hazard Communication Standard 29CFR 1910-1200 and it does not necessarily imply the existence of hazard. The chemicals or compounds reportable by Section 313 of SARA are marked by the symbol #.

## 4. FIRST AID MEASURES:

Sheet

**Inhalation**: Remove to fresh air immediately or administer oxygen. Get medical attention immediately. **Skin**: Flush skin with large amounts of water. If irritation develops and persists, get medical attention.

**Eye:** Flush eyes with water for at least 15 minutes. Get medical attention. **Ingestion:** Obtain medical attention immediately if ingested. Rinse mouth.

**Electric Shock:** Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. Immediately contact a physician.

## 5. FIRE-FIGHTING MEASURES:

**Suitable Extinguishing Media:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Welding arcs and sparks can ignite combustible and flammable materials. Use the extinguishing media recommended for the burning material and fire situation.

**Unsuitable Extinguishing Media:** Do not use water on molten metal. Large fires may be flooded with water from a distance.

**Specific Hazards Arising From Chemical:** Keep away from heat/spark/open flames/hot surfaces – No smoking. Iron-oxides, Aluminum oxide, Silicon Oxides, Manganese/manganese oxides

**Protective Equipment:** Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Personal Precautions: Refer to section 8. Environment Precautions: Refer to section 13.

**Cleaning Measures:** Solid objects may be picked up and placed into a container. Liquids or pastes should be scooped up and placed into a container. Wear proper protective equipment while handling these materials. Do not discard as refuse.

# 7. HANDLING AND STORAGE:

**Precautions for Safe Handling:** Handle with care to avoid stings or cuts. Wear gloves when handling welding consumables. Avoid exposure to dust. Do not ingest. Some individuals can develop an allergic reaction to certain materials. Retain all warning and identity labels.

**S**afety Latest Revision: June 2015

**D**ata Page 3 of 7

**S**heet Hobart Brothers Co.

# 

**Conditions for Safe Storage:** Store in dry place in closed packages. Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions.

# 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION:

**Engineering Controls:** Avoid exposure to welding fumes, radiation, spatter, electric shock, heated materials and dust. Ensure sufficient ventilation, local exhaust, or both, to keep welding fumes and gases from breathing zone and general area. Keep work place and protective clothing clean and dry. Train welders to avoid contact with live electrical parts and insulate conductive parts. Check condition of protective clothing and equipment on a regular basis.

**Exposure limits:** Use industrial hygiene equipment to ensure that exposure does not exceed applicable national exposure limits. The limits defined under section 3 can be used as guidance. Unless noted, all values are for 8 hour time weighted average. For information about welding fume analysis refer to section 10.

Biological limits: No available data

Personal protection:

**Respiratory protection:** Use an air purifying dust respirator when welding or brazing in a confined space, or when local exhaust or ventilation is not sufficient to keep exposure values within safe limits.

**Hands protection:** Wear appropriate gloves to prevent skin contact.

**EN 12477: Protection gloves for welders** 

Requirements (EN Levels)	Type A	Type B
Abrasion (Cycles)	2 (500)	1 (100)
Cut (Factor)	1 (1.2)	1 (1.2)
Tear (Newton)	2 (25)	1 (10)
Puncture (Newton)	2 (60)	1 (20)
Burning Behaviour	3	2
Contact Heat	1	1
Convective Heat	2	-
Small Splashes	3	2
Dexterity	1 (11)	4 (6.5)

Type B gloves are recommended when high dexterity is required as for TIG welding, while type A gloves are recommended for other welding processes. The contact temp (°C) is 100 and the threshold time (seconds) >15.

**Eyes protection:** Welder's helmet or face shield with colour absorbing lenses. Shield and filter to provide protection from harmful UV radiation, infra red and molten metal approved to standard EN379. Filter shade to be a minimum of shade 9.

**Skin protection:** Heat-resistant protective clothing. Wear safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry. Clothing should be selected to suit the level, duration and purpose of the welding activity.

Class 1		
Impact of Spatter	15 Drops	
Heat Transfer (radiation)	RHTI 24 ≥ 7 seconds	
Process	Manual welding with light formation of spatter and drops     Gas Welding     TIG Welding     MIG Welding     Micro plasma welding     Brazing     Spot Welding     MMA Welding (with rutile-covered electrode)	

**S**afety Latest Revision: June 2015

**D**ata Page 4 of 7

**S**heet Hobart Brothers Co.

# 

Environmental	Operation of machines	
Conditions	Oxygen cutting machines	
	Plasma cutting machines	
	Resistance welding machines	
	Machines for thermal spraying	
	Bench welding	

Class 2			
Impact of Spatter 25 Drops			
Heat Transfer (radiation)	RHTI 24 ≥ 16 seconds		
Process	Manual welding with heavy formation of spatter and drops  MMA welding (with basic or cellulose-covered electrodes)  MAG welding (with CO2 or mixed gases)  MIG Welding (with high current)  Self shielded flux core arc welding  Plasma cutting  Gouging  Oxygen cutting  Thermal spraying		
Environmental	Operation of machines		
Conditions	In confined spaces		
	<ul> <li>At overhead welding/cutting or in comparable constrained positions</li> </ul>		

# 9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Solid.

Color: Green 1059/Black 1155/ Gold 1159/Blue 1160/ Tan 1168/Red 1171/ Violet

**Odour:** Odourless

Odour Threshold: Not Available

pH Value: Not Available

Melting Point/Melting Range: : >2300° F, >1300° C

Freezing Point: Not Available

Boiling Point/Boiling Range: Not Available

Flash point: Not Available

Evaporation Rate: Not Available Self-in flammability: Not Available Explosion limits: Not Available Vapour pressure: Not Available Vapour density: Not Available Density at 20°C: Not Available Relative density: 6-9 g/cm3 Solubility: Insoluble in water.

Partition coefficient: Not Available
Auto-ignition temperature: Not Available
Decomposition temperature: Not Available

Other Information: No available data.

# 10. STABILITY AND REACTIVITY:

**Chemical Stability:** This product is stable under normal conditions.

**S**afety Latest Revision: June 2015

**D**ata Page 5 of 7

Sheet Hobart Brothers Co.

# 

Hazardous Reactions: Contact with chemical substances like acids or strong bases cause generation of gas.

Conditions to Avoid: Not applicable. **Incompatible Materials:** Reacts with acid.

Hazardous Decomposition Products: When this product is used in a welding process, hazardous decomposition product would include those from volatilization, reaction or oxidation of the material listed in section 3 and those from the base metal and coating. The amount of fumes generated from this product varies with welding parameters and dimensions.

Refer to applicable national exposure limits for fume compounds, including those exposure limits for fume compounds found in section 3. Manganese has a low exposure limit, in some countries that may be easily exceeded. Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quality of fumes and gases produced.

# 11. TOXICOLOGICAL INFORMATION:

Signs and Symptoms of Overexposure: Inhalation of welding fumes and gases can be dangerous to your health. Classification of welding fumes is difficult because of varying base materials, coatings, air contaminants and processes. The Internal Agency for Research on Cancer has classified welding fumes as possible carcinogenic to humans (Group 2B).

**Acute Effects:** Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes. May cause sensitisation by skin contact

LD/LC50 Values that are relevant for classification		
Cellulose 9004-34-6		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

LD/LC50 Values that are relevant for classification		
Manganese 7439-96-5		
Oral LD50 9000 mg/kg (rat)		

LD/LC50 Values that are relevant for classification		
Titanium Dioxide 13463-67-7		
Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)

LD/LC50 Values that are relevant for classification		
Iron 7439-89-6		
Oral	LD50	30000 mg/kg (rat)

Chronic Effects: Overexposure to welding fumes may affect pulmonary function and eyes. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait. Prolonged inhalation of titanium dioxide (Classified 2B by IARC) above safe exposure limits can cause cancer.

# 12. ECOLOGICAL INFORMATION:

**Toxicity:** Welding rods contain metals which are considered to be very toxic towards aquatic organisms. Finely divided welding rods are therefore considered harmful to aquatic organisms.

**Persistence and Degradability:** The welding rods consist of elements that can not degrade any further in the environment. Bio accumulative Potential: Welding rods contain heavy metals which bio accumulates in the food chain. The following figures are the bio concentration factor (BCF) for the substances on their own. BCF:

Iron, BCF: 140000

**S**afety Latest Revision: June 2015

**D**ata Page 6 of 7

**S**heet Hobart Brothers Co.

Manganese, BCF: 59052

**Mobility in Soil:** Welding rods are not soluble in water or soil. Particles formed by working welding rods can be transported in the air.

Other Adverse Effects: In massive form, welding rods present no hazards to the aquatic environment.

Welding materials could degrade into components originating from the materials used in the welding process. Avoid exposure to conditions that could lead to accumulation in soils or groundwater. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS:

**Product:** For product elimination, consult recycling companies or appropriate local authority.

**USA RCRA:** This product is not considered hazardous waste if discarded. Residue from welding consumables and processes could degrade and accumulate in soils and groundwater.

**Package:** May be disposed in approved landfills provided local regulations are observed.

## 14. TRANSPORT INFORMATION:

**UN-number:** Welding rods are not classified as dangerous goods for transport and has no UN number.

**UN proper shipping name:** Welding rods are not classified as dangerous goods for transport and has no UN proper shipping name.

**Transport hazard class:** Welding rods are not classified as dangerous goods for transport.

**Packing group:** There are not any special precautions with which a user should or must comply or be aware of in connection with transport or conveyance either within or outside premises.

**Environmental hazards:** Welding rods are not environmentally hazardous according to the criteria of the UN Model Regulations (as reflected in the IMDG Code, ADR, RID and AND) and/or a marine pollutant to the IMDG Code.

**Special precautions for users:** There are not any special precautions which a user should or must comply or be aware of in connection with transport or conveyance either within or outside premises of the welding rod.

**Transport in Bulk According to Annex III MARPOL 73/78 and the IBC Code:** Welding rods in massive form do not subject under MARPOL 73/78 and the IBC Code. Not applicable – product is transported only in packaged form.

## **15. REGULATORY INFORMATION:**

**Safety, health and environment regulations/legislation specific for the substance or mixture:** Read and understand the manufacturer's instructions, your employer's safety practices and the health and safety instructions on the label. Observe any federal and local regulations. Take precautions when welding and protect yourself and others.

**Warning:** Welding fumes and gases are hazardous to your health and may damage lungs and other organs. Use adequate ventilation. Electric shock can kill. Arc rays and sparks can injure eyes and burn skin. Wear correct hand, head, eye and body protection.

## Chemical safety assessment: No

USA: Under the OSHA Hazard Communication Standard, this product is considered hazardous. This product contains or produces a chemical known to the state of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code § 25249.5 et seq.) United States EPA Toxic Substance Control Act: All constituents of this product are on the TSCA inventory list or are excluded from listing.

## **EPCRA/SARA Title III Toxic Chemicals**

The following metallic components are listed as SARA 313 "Toxic Chemicals" and potential subject to annual SARA reporting. See Section 3 for weight percentage.

Ingredient Name	Disclosure Threshold
Manganese	5 mg/m3

**S**afety Latest Revision: June 2015

**D**ata Page 7 of 7

**S**heet Hobart Brothers Co.

# 

### 16. OTHER INFORMATION:

The information in this document is believed to be correct as of the date issued. However, no warranty is expressed to be implied regarding the accuracy or completeness of this information. This information and product are furnished on the condition that the person receiving them shall make his own determinations as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

This Material Safety Data Sheet complies with the EC directives 91/155/EEC and 93/112/EEC, including modifications 2001/58/EC.

Complies with OSHA Communication Standard 29 CFR 1910.1200 and Superfund Amendments and Reauthorization Act (SARA) of 1986 Public Law 99-499

### **Hazard Statements:**

**H315** – Causes skin irritation.

**H319** – Causes serious eye irritation.

**H351** – Suspected of causing lung cancer.

H373 – May cause damage to organs through prolonged or repeated exposure.

### **R-Phrases:**

R36/38 – Irritating to eyes and skin.

**R40** – Limited evidence of a carcinogenic effect.

**R48** – Danger of serious damage to health by prolonged exposure.

**S-Phrases:** 

**S36/37** – Wear suitable protective clothing and gloves.

S43 – In case of fire, use fire-fighting equipment on basis class D.

End of the document.