

# Flow Gauge Regulator 10–50 scFH

With 5-foot Gas Hose



287705  
February 2020



770971

## Includes

- Flow gauge regulator 10–50 scfh
- 5-foot (1.5 m) reinforced PVC gas hose with fittings

**Durable and accurate industrial-grade regulator designed for extended life.**

## Medium-Duty Regulator

- Dual filters protect seat from debris for reliable operation
- Auto-resetting relief valve releases damaging excess pressure
- Anodized aluminum body and bonnet for corrosion resistance
- Neoprene diaphragm for precise pressure adjustment
- Shatter-resistant polycarbonate gauge lenses
- 2-inch (51 mm) diameter gauges with dual-scale readings
- For use with 100% argon and argon/CO<sub>2</sub> mixed gases
- 100% tested and inspected
- One-year warranty
- UL listed, assembled in USA

## Inert Gas Hose

- Smooth interior and exterior to prevent sediment accumulation
- Open-weave innerbraid for increased working pressures
- Smooth-bore and full-flow ID for standard barbed fittings

## Applications

- MIG welding
- TIG welding

## Regulator Specifications

Gas	Flow Range	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection	Max. Inlet Pressure
100% argon and argon/CO <sub>2</sub> mixed gases	10–50 scfh (5–24 lpm)	0–4,000 psig (0–276 bar)	10–50 scfh (5–24 lpm)	CGA 580	Barbed	3,000 psig (207 bar)

## Hose Specifications

Hose Type	Length	Inside Diameter	Connection to Machine	Color	Material	Reinforcement
For inert gas	5 ft. (1.5 m)	3/16 in. (5 mm)	5/8"-18 UNF, male thread	Clear	Reinforced PVC	Polyester fiber

Note: Specifications subject to change without notice.



## Hobart Welding Products

An ITW Welding Company  
Sales: 800-626-9420  
Service: 800-332-3281

HobartWelders.com

